

VERTICAL BRACKET SET



The Vertical Bracket set is installed on the top and bottom of a permanent ladder. The maximum rung diameter is 3,5 cm. All the fixing elements are included.

SHOCK ABSORBER



Cleaning & maintenance

Products do not require any special maintenance, aside from cleaning. Cleaning of your SDA product is important to prolong its lifetime. Use cold water and soap to eliminate all type of residue (dirt, chemicals, etc.). Dry gently out of sunlight. After use, place your product in a well-ventilated area and avoid excessive heat. Proper care prevents premature wear of the equipment.

Inspection

Look for damage, deterioration or malfunction before and after every use. Inspections should only be made by trained and authorized personnel. Every inspection should be registered in the product dossier.

Anchorage :	Top Bracket Long :	Top Bracket Short :	Bottom Bracket :	Mounting Top Bracket :
<ul style="list-style-type: none">• 16 Stainless steel screws, nuts, washers, 3 plates and 5 counterplates.• 3 plates y 8 U-brackets.	2100 x 40 x 40 mm	1200 x 40 x 40 mm	650 x 40 x 40 mm	<ul style="list-style-type: none">1 Fixed bottom position with u-bracket.2 adjustable positions with plate and counterplates / u-bracket and plate.
Mounting Bottom Bracket :	Color :	Top Bracket :	Bottom Bracket :	Article Number:
<ul style="list-style-type: none">1 Fixed bottom position with u-bracket.1 adjustable position with plate and counterplates / u-bracket and plate.	Chrome	Galvanized steel / Stainless steel*	Galvanized steel / Stainless steel	<ul style="list-style-type: none">(1,2 m Galvanized. Steel) 661000-G(2,1 m Galvanized. Steel) 662000-G(1,2 m Stainless steel) 661000-SS(2,1 m Stainless steel) 662000-SS