

ANCHOR STRAP WITH SLEEVE



Anchor strap with sleeve made of high tenacity polyester webbing, with 1 D-ring & loop. 3ft (0.9m) length.

(All products available in other lengths)

ANCHOR STRAP WITH SLEEVE



Cleaning & maintenance

Products do not require any special maintenance, aside from cleaning. Cleaning of your SDA product is important to prolong its lifetime. Use cold water and soap to eliminate all type of residue (dirt, chemicals, etc.). Dry gently out of sunlight. After use, place your product in a well-ventilated area and avoid excessive heat. Proper care prevents premature wear of the equipment.

Inspection

Look for damage, deterioration or malfunction before and after every use. Inspections should only be made by trained and authorized personnel. Every inspection should be registered in the product dossier.


Type:	Webbing material:	D-rings:	Color:	Norm:
Fall protection	Polyester	1	+20 available colors	ANSI Z359.18-2017

Product life expectancy


The life expectancy of this product is 5 years from the date of first use recorded on the inspection label, if this date is not recorded, it will be counted from the date of manufacture.

The product is subject to an inspection before each use by the user and at least once a year by a competent person in accordance with current national and international standards. The inspector must be certified by SDA and will determine if the product is suitable for use.

Fall factor



Fall factor 0:
Anchor strap positioned above user's connection point



Fall factor 1:
Anchor strap positioned at the same level of user's connection point