

# FALL ARREST CABLE LANYARD

---



Fall protection lanyard made of steel 1/4" (6mm) cable. 6ft. (1.8m) length with 1 x 3/4" & 2 x 1 1/4" steel hooks.

---

# FALL ARREST CABLE LANYARD



## Cleaning & maintenance

Products do not require any special maintenance, aside from cleaning. Cleaning of your SDA product is important to prolong its lifetime. Use cold water and soap to eliminate all type of residue (dirt, chemicals, etc.). Dry gently out of sunlight. After use, place your product in a well-ventilated area and avoid excessive heat. Proper care prevents premature wear of the equipment.

## Inspection

Look for damage, deterioration or malfunction before and after every use. Inspections should only be made by trained and authorized personnel. Every inspection should be registered in the product dossier.

Type:	Cable material:	Hooks:	Color:	Norm:
Fall protection	Steel	Steel 1 x 3/4" & 1 x 2 1/4" hardware	+20 available colors	ANSI Z359.13-2013

## Product life expectancy

The life expectancy of this product is 5 years from the date of first use recorded on the inspection label, if this date is not recorded, it will be counted from the date of manufacture.

The product is subject to an inspection before each use by the user and at least once a year by a competent person in accordance with current national and international standards. The inspector must be certified by SDA and will determine if the product is suitable for use.

## Special notes

The product should always be protected from sharp edges and abbrasive surfaces. Keep the lanyard as short as possible to reduce the falling distance. Try to limit the free fall to a maximum of 1.2 m (4 ft).