

DP POST



The DP Post is the best solution for lifelines on roofs. The conical shape uses the deformation of the wall for energy absorption, additionally it has an internal absorber to further reduce the resulting force on the structure in case of a fall. The cone can be screwed onto diverse base plates (squared, round or rigid) used according to the roof type.

Cleaning & maintenance

Products do not require any special maintenance, aside from cleaning. Cleaning of your SDA product is important to prolong its lifetime. Use cold water and soap to eliminate all type of residue (dirt, chemicals, etc.). Dry gently out of sunlight. After use, place your product in a well-ventilated area and avoid excessive heat. Proper care prevents premature wear of the equipment.

Inspection

Look for damage, deterioration or malfunction before and after every use. Inspections should only be made by trained and authorized personnel. Every inspection should be registered in the product dossier.

Weight :	Breaking Strength :	Anchorage :	Dimensions :	Marking :
2.3 kg.	40,0 kN	M12	Height: 207 mm Diameter: 262 mm	Serial number on safety nut
Post :	Base Plate :	Absorber :	Sealing Disk :	Surface Treatment :
Aluminium 3 mm (powder coating)	Aluminium 3 mm	Stainless Steel 316	Electropolished	Electropolished
Packaging :	Testing :	Anchor :	Color :	Article Number :
1 or 2 per box, base plate separated(max. 6 per box)	EN 795-C	Stainless Steel 316	Custom colors available on request	DP 621000-XL DP End Point 621020-XL DP Intermediate 621030-XL DP Intermediate 45° 621024-XL DP Intermediate 90° 621055-XL