## 6 FT DYNEEMA WEBBING LE SRL





High-impact strength Polymer Housing with Dyneema (UHMPE) webbing, and a steel swivel hook.  $2.48" \times 3.74"/6.3 \text{ cm } \times 9.5 \text{ cm}$  size, 6 ft / 1.8 m length webbing.

## 6 FT DYNEEMA WEBBING LE SRL



## **Cleaning & maintenance**

Products do not require any special maintenance, aside from cleaning. Cleaning of your SDA product is important to prolong its lifetime. Use a damp cloth if necessary.

## Inspection

Look for damage, deterioration or malfunction before and after every use. Inspections should only be made by trained and authorized personnel. Every inspection should be registered in the product dossier.

Type:	Housing:	Webbing:	Weight:	Max. arresting distance:	Norm:
Fall protection	High-impact strength Polymer	Dyneema (UHMPE) webbing	2.80 lbs / 1.30 kg	42" / 106.6 cm	ANSI Z359.14-2021 Class 2

Capacity range:	Average arresting force:	Max. arresting force:	Max. free fall distance:
130 - 310 lbs / 59 - 140 kg	1350 lbs / 612 kg	1800 lbs / 816 kg	2 ft / 60 cm

	Acc	esories:	

Carabiner